

GreenClean 8500



BIODEGRADABLE CLEANER

For Professional Use Only

GSP DOCUMENT NO.: TDS 2017030

PRODUCT DESCRIPTION

GreenClean 8500 BioDegradable Cleaner (BDC) is a water soluble concentrate designed to clean a wide variety of construction surfaces. BDC contains cleaning agents that effectively remove dirt from roofs, walls and floors prior to the application of construction coatings. It is a non-toxic, bio-based environmentally friendly product.

PACKAGING

Available as a 5 gallon container of concentrate.

TECHNICAL DATA

Color: Light Amber (Concentrate), Clear (Diluted)
pH: 8.7 (Concentrate), Neutral (Wash Runoff)
Biobased Content: >65%

USES

BDC can be used to clean aged (minimum 30 day cure) acrylic, epoxy, polyurethane, and silicone roof and wall, and floor surfaces. It can also be used to clean uncoated surfaces like concrete, masonry, and metal.

APPLICATION (STANDARD CLEANING)

1. Dilute the BDC concentrate with 10 parts water to 1 part cleaner.
2. Apply the diluted cleaning solution to the substrate needing cleaning at a rate of between 150 to 200 square feet per gallon. Allow the solution to stand for 15 minutes. Do not allow the solution to dry. Areas with heavy dirt build up may require additional solution as well as scrubbing with a stiff-bristled broom.

3. Before cleaner dries, rinse the surface under high pressure with clear water. Rinse thoroughly until cleaning solution has been fully removed. Superior cleaning may be achieved by using an extension wand and standard spray tip in proximity to the substrate.
4. Repeat the clean and rinse process until the desired surface finish is achieved.
5. Allow the substrate to fully dry before applying any type of coating.

APPLICATION (SPOT CLEANING)

1. In areas with very heavy dirt buildup, BDC may be used in its fully concentrated form. Apply a small amount of solution to the affected area and scrub with a stiff-bristled broom.
2. Before cleaner dries, rinse the surface under high pressure with clear water. Rinse thoroughly until cleaning solution has been fully removed. Superior cleaning may be achieved by using an extension wand and standard spray tip in proximity to the substrate.
3. Repeat the clean and rinse process until the desired surface finish is achieved.
4. Allow the substrate to fully dry before applying any type of coating.

APPROVALS

U.S. EPA DfE: Product is manufactured from materials recognized by the US Environmental Protection Agency in their Design for the Environment (DfE) program.

HEALTH AND SAFETY

Read the Safety Data Sheet (SDS) and container label for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

TECHNICAL DATA SHEET

To the best of our knowledge all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. Contact Green Shield Products, LLC to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Green Shield Products, LLC. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY Green Shield Products, LLC EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE

Green Shield Products, LLC

4008 Louetta Rd. #464 Spring, TX 77388-4405 (P) 832-957-2925 (F) 832-957-3960

www.greenshieldproducts.com